

Dulux TRADE

DULUX TRADE CLASSIC SELECT WOODSTAIN

Issued July 2010

609

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Classic Select Woodstain protects and decorates exterior smooth planed wood and rough sawn timber. This woodstain is deep-penetrating and provides a low build matt finish which will not blister or flake. It offers protection for up to four years and is suitable for hardwoods and softwoods.</p> <p>In common with other low build stains, the Dulux Trade Classic Select Woodstain is not recommended for areas of severe exposure and will require more frequent maintenance than a medium build woodstain.</p> <p>Before preparing any surface for painting, read the Health Safety & Environmental information on page 2 about old lead-based paints.</p>	
Pack Size	1, 2.5 and 5 Litre.	
Colour Range	See appropriate Dulux Trade colour literature.	
Composition (nominal)	Pigment:	Special Transparent Iron Oxide Micro Pigments and Organic Pigments.
	Binder:	Alkyd and a Fungicide, for the purpose of protecting the film.
	Solvent:	Low Odour Aliphatic Hydrocarbons.
Volume Solids	16% (nominal), colours will vary.	
Application Method	Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.	
Thinning	Do not thin this product.	
Film Thickness	Film thickness will be dependent upon the coverage achieved. A nominal figure at 14m ² per litre will give a wet film thickness of 71 microns.	
Drying Times	<i>Single coat at standard thickness:</i>	
	Touch Dry:	4-6 hours.
	Recoat:	16 hours.
Practical Coverage	On surfaces of average porosity a litre of stain is sufficient to apply one coat to an area of up to 14m ² . This figure will vary greatly depending upon the porosity of the wood.	
Cleaning Up	After use, remove as much woodstain as possible from brushes before cleaning with white spirit.	
	Do not use or store in extremes of temperature.	

SURFACE PREPARATION

Surfaces generally must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Surfaces that have been previously painted or varnished must be stripped back to bare wood. All surfaces should be thoroughly rubbed down using a suitable abrasive paper, (working in the direction of the grain) and then dusted off (refer to your COSHH Assessment). All screws, nails and other fixings must be non-ferrous.

Where a low build woodstain has been used on the exterior of joinery and has eroded and weathered and the wood is split, remove defective coatings, glazing materials and beading. Remove any mould, algae, lichen or moss and then treat the surface with ***Weathershield** Multi-Surface Fungicidal Wash. Clean all rebates and rub down all surfaces in the direction of the grain and dust off. Do not use linseed oil putty for glazing (or making good) with natural wood finishes, use external beads set in an appropriate non-setting mastic or a special glazing compound.

It is essential to apply a first coat to the back of cladding, edges of window frames before fixing into the building etc. Ensure that all endgrain, top and bottom edges of doors, undersides of sills etc all receive a liberal coat.

For best results use only on joinery manufactured in accordance with BS EN 942: 1996 parts 1 & 2. (or as amended) 'Quality of Timber and Workmanship in Joinery'. Failure to prepare the surface as described above or apply the recommended number of coats will impair the performance of the system and lead to premature failure or maintenance.

SYSTEM INFORMATION

Stir thoroughly before use.

Apply 2 or 3 full coats of the **Dulux Trade** Classic Select Woodstain.

A factory applied preservative pretreatment is recommended for softwood and non-durable hardwoods. If in doubt, 2 coats of **** Weathershield** Preservative Basecoat+ can be applied to bare exterior wood.

To optimise the dimensional stability, water repellency and durability on exterior joinery, particularly in areas of severe exposure the use of **Dulux Trade** Protective Woodsheen or **Weathershield** Ultimate Woodstain is recommended.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

SOLVENT-BASED WOODSTAIN

THIS PRODUCT IS FOR EXTERIOR USE ONLY

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

Contains: ethyl methyl ketoxime, dichlofluanid, cobalt carboxylate. May produce an allergic reaction.

Keep away from sources of ignition - no smoking.

Contains white spirit. Use only in well ventilated areas.

When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Avoid release to the environment. Refer to special instructions/Safety data sheet.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

***Weathershield** Multi-Surface Fungicidal Wash contains:

Benzalkonium Chloride

****Weathershield** Preservative Basecoat+ contains:

Dichlofluanid.

Use biocides safely. Always read the label and product information before use.

EU limit value for this product (cat.A/f):700g/l (2007)/700g/l (2010).

This product contains max.699g/l VOC

See www.duluxtrade.co.uk

VOC Content Very High more than 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, Weathershield, AP and the ICI Roundel are Trademarks of AkzoNobel.

© AkzoNobel 2010 (06072010IT SDS609)

