

PRODUCT DESCRIPTION & USE

Armstead Trade Anti-Mould Vinyl Matt is a professional quality, tough and durable matt emulsion that minimises surface imperfections. Suitable for all normal interior wall and ceiling surfaces, especially those at risk of disfigurement due to mould growth.

KEY BENEFITS

- **Helps to reduce the growth of mould & algae**
- **Good opacity**
- **For interior walls & ceilings**

PACK SIZES



COLOUR RANGE

Armstead Trade Exclusive:	150 colours
BS4800:	99 colours
RAL:	45 colours
NCS 1 & 2:	843 colours
Visit www.armsteadtrade.co.uk/pp	

FILM PROPERTIES

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces e.g. radiators.

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments.

COMPOSITION (NOMINAL)

Pigment:	Lightfast Pigments.
Binder:	Acrylic Copolymer Emulsion.
Solvent:	Water.

VOLUME SOLIDS

31% (nominal).

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. Treat any existing mould or organic growth with *Weathershield Multi-Surface Fungicidal Wash. New plaster and masonry must be fully dry before priming.

Note: Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Brush or roller. For Health and Safety reasons related to all fungicidal paints, spray application is not recommended.

As with other water-based paints, do not apply in temperatures below 8°C (as recommended by British Standard BS 6150)

SYSTEM INFORMATION

Stir thoroughly before use.

On very absorbent surfaces apply a sealing coat of thinned **Armstead Trade** Anti-Mould Vinyl Matt.

Finishing:

Apply 1 or 2 coats of **Armstead Trade** Anti-Mould Vinyl Matt.

PRACTICAL COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 14m²/litre.

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry:	1-2 hours*
Recoat:	2-4 hours*

*Dependent upon temperature & humidity

CLEANING UP



After use, remove as much paint as possible from equipment before cleaning with clean water.

TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat A/a): 30 g/l (2010) This product

***Weathershield** Multi-Surface Fungicidal Wash contains: Benzalkonium Chloride.

Use biocides safely. Always read the label and product information before use.

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

FURTHER SUPPORT

Online: www.armsteadtrade.co.uk
Email: armstead_advice@akzonobel.com
Phone: 08444-817-818

Please visit www.armsteadtrade.co.uk to download safety sheet SDSAM213



Like us on Facebook



Videos on YouTube



Follow us on Twitter



Download on the App Store



Let's create together a better future for our planet.
Find out how at: www.armsteadtrade.co.uk/pp