

DESCRIPTION

Acrylic Satin is a premium quality satin sheen finish that is suitable for interior use on wood and suitably primed metal surfaces. It provides a low odour, high opacity finish that is quick drying and non-yellowing.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Over 15,500 colours are available via the Johnstone's Tinting System.

FINISH

Satin.

VOLUME SOLID

35%

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from Frost.

THINNER

Clean water.

VOC CONTENT

Medium VOC content 8-24.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 150g/l (2007) / 130g/l (2010).
This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 80µm, dry: 28µm.

KEY PROPERTIES

- Non yellowing.
- High opacity.
- Quick drying.
- Low odour satin finish.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat knots with Knotting Solution and prime exposed wood and metal with an appropriate primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well before use and apply by brush or roller. Apply liberally and evenly for a smooth finish. Two coats are recommended under most conditions. Do not apply in temperatures below 10°C or in damp conditions.

CLEANING



Remove as much paint as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.