

DESCRIPTION

Johnstone's Alkali Resisting Primer is a solvent-based primer and sealer formulated for interior and exterior use on new or bare plaster, concrete, cement and rendered surfaces. Used as a primer on unpainted surfaces and as a sealer on powdery substrates it provides exceptional resistance to alkali attack.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Plaster, concrete, cement rendering, brick, stone and blockwork.

COLOUR RANGE

White.

FINISH

N/A.

VOLUME SOLID

48%

COVERAGE



Approximately 9–11 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 4–6 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

High VOC content 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 450g/l (2007).
This product contains max 450g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 48µm.

KEY PROPERTIES

- Binds powdery surfaces and resists alkali attack.
- An ideal primer for unpainted plaster and rendered surfaces.
- Suitable for interior and exterior use.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **FLAMMABLE**
- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – Do not use solvent or thinners.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear suitable respirator or air fed respiratory equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

SIZES

2.5 Litre, 5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.