

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF070 Blackfriar Exterior Water Seal.**

Updated  
09/02/2011

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b></p> <p>A clear coating which is designed to repel water and prevent it penetrating exterior walls.</p> <p><b><u>Usage/purpose</u></b></p> <p>For use on surfaces such as brickwork, cement and mortar.</p> <p><b><u>Characteristics</u></b></p> <p>A clear finish which seals substrates to prevent moisture penetrating.</p> <p><b><u>Finish</u></b></p> <p>Clear</p> <p><b><u>Colour(s)</u></b></p> <p>Clear.</p> <p><b><u>Packaging</u></b></p> <p>5 litre.</p> <p><b><u>Disclaimer;</u></b></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b></p> <p>A silicone based resin dissolved in a blend of organic solvents.</p> <p><b><u>Properties</u></b></p> <p>EU limit value for this product (cat A/h): 750 g/l . This product contains max 750 g/l VOC</p> <p><b><u>Performance</u></b></p> <p>For exterior use on surfaces after thorough preparation.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the surface to be treated is clean, sound and firm, with any cracks filled. Do not use alkaline or acid detergents or cationic surfactants. It is advisable to wait 28 days before treating fresh masonry.</p> <p><b><u>Application Method</u></b></p> <p>Apply 1 coat liberally by brush, roller or spray until the surface is saturated: Blackfriar Exterior Water Seal should drip down 30cm. On very porous surfaces a second coat is necessary as soon as the first one has lost its glossy appearance.</p> <p><b><u>Recommended Spreading Rate</u></b></p> <p>Approximately 2-4m<sup>2</sup>/L depending on the porosity of the substrate</p> <p><b>For Technical Enquiries, Material Safety Data Sheets Telephone 0191 4113146</b></p>	<p><b><u>Thinning</u></b></p> <p>Not necessary.</p> <p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Leave overnight before re-coating under normal conditions (20°C 50% r/h).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><b><u>Limitations</u></b></p> <p>Not suitable for use over wood, metal or limestone.</p> <p><b><u>Environmental Info.</u></b></p> <p>Flammable</p> <hr/> <p>Paint Product UN No. 1139.</p> <hr/> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>
--	--	--