

PRODUCT DESCRIPTION & USE

Armstead Trade Primer Sealer is a professional quality primer sealer with good alkali resisting properties, designed to seal porous, dry and friable surfaces.

KEY BENEFITS

- **Alkali resisting properties**
- **Seals porous, dry & friable surfaces**
- **For interior walls & ceilings**

PACK SIZES



COLOUR RANGE

Off-white.

COMPOSITION (NOMINAL)

Pigment:	Titanium Dioxide and inert extenders.
Binder:	Oleoresin.
Solvent:	White Spirit.

VOLUME SOLIDS

49% (nominal).

SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, efflorescence, dirt, grease, wax etc. Where necessary surfaces should be rubbed down using a suitable abrasive paper and then dusted off (refer to your COSHH Assessment).

Note: Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

SYSTEM INFORMATION

Stir thoroughly before use.

After suitable preparation, the normal recommendation is to apply one coat of **Armstead Trade** Primer Sealer, followed by the appropriate **Armstead Trade** finishing system.

PRACTICAL COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 9m²/litre.

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



Touch Dry: 8-12 hours*
Recoat: 16-24 hours*

*Dependent upon temperature and humidity

CLEANING UP



After use, remove as much paint as possible from brushes before cleaning with white spirit.

TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat A/h): 750g/l (2010). This product contains max. 425g/l VOC.

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

FURTHER SUPPORT

Online: www.armsteadtrade.co.uk
Email: armstead_advice@akzonobel.com
Phone: 08444-817-818

Please visit www.armsteadtrade.co.uk to download safety sheet SDSAM104



Like us on Facebook



Videos on YouTube



Follow us on Twitter



Download on the App Store



Let's create together a better future for our planet.
Find out how at: www.armsteadtrade.co.uk/pp