

## DESCRIPTION

A universal road marking paint suitable for application to asphalt, concrete and bricks. Its fade resisting properties and rapid drying make it ideal for use on roads, runways, car parks and sports facilities.

## RECOMMENDED USES



Line marking requirements on roads, runways, car parks and sports facilities.

## SPECIAL PROPERTIES

High build, good coverage and wear resistance. Also has good skid resistance. Rapid drying.

## COLOUR RANGE

White and Yellow.

## FINISH

Matt.

## VOLUME SOLID

50%

## COVERAGE



Johnstone's Road Marking Paint will cover at the rate of approximately 2.3–2.6 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 10 minutes. Hard dry after 30 minutes. Recoatable after 1 hour.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## CLEANER

TC1 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 600g/l (2007) / 500g/l (2010). This product contains max 500g/l VOC.

## FILM THICKNESS

Wet: 380–440µm, dry: 190–220µm.

## SIZE

5 Litre

## PREPARATION

All surfaces to be painted should be dry and free from dust, salts, grease and other contaminants prior to application.

## APPLICATION



Stir thoroughly before use. Apply evenly using a clean, well loaded brush. To ensure correct thickness is achieved, do not attempt to brush out or lay off.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with TC1 Thinner and Cleaner. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT
- Contains Xylene.
- FLAMMABLE.
- HARMFUL BY INHALATION AND IN CONTACT WITH THE SKIN.
- IRRITATING TO SKIN.
- Keep away from sources of ignition – No smoking.
- Use only in well ventilated areas.
- Do not breathe vapour.
- In case of insufficient ventilation, wear suitable respiratory protective equipment.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

