

BLACKFRIAR PAINTS
TECHNICAL DATA SHEET
BF043 **Blackfriar Problem Solving Primer.**

Revision date: 24/03/2010

Product Information

Description

A water based primer with excellent stain blocking properties. Interior and exterior use.

Usage/purpose

Specifically formulated to provide good adhesion to a wide range of substrates. Surfaces include non ferrous metals, concrete, plaster, some plastics, ceramic tiles and wood. Excellent undercoat for hanging wallpapers. Suitable for priming galvanised steel without pre-treatment.

Characteristics

An excellent stain blocking primer for covering nicotine, dried water, soot, wood tannins and bitumen.

Finish

Matt Finish

Colour(s)

White

Packaging

500ml, 1litre, 2.5litre.

Disclaimer;

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.

Technical Spec

Composition

Water based resin technology.

VOC

EU limit value for this product (cat A/g): 30 g/l (2010). This product contains max 30 g/l VOC

Performance

Excellent substrate and intercoat adhesion properties. Compatible with conventional single pack paint systems.

Surface Preparation

Ensure the substrate to be painted is dry, sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc).

Application Method

Brush, roller, airless spray
Ensure product is thoroughly stirred with a broad stirrer. Apply one or two coats as required.

**For Material Safety Data Sheets.
Contact Sales on 0191 4106611
For Technical Enquiries
Telephone 0191 4106611**

Recommended Spreading Rate

For optimum stain blocking, 2 coats required. 9-11m²/ltr .

Thinning

Dilution with water adversely affects stain blocking properties.

Drying Time

Touch dry in 1hour.
Recoat after 4-6 hours under normal conditions (20°C 50% RH).

Cleaning

Clean application equipment or spills with water.

Limitations

Problem solving primer is not compatible with other products. Always use clean brushes and tools. Do not expose to rain. Not suitable for application to whitewash. Not suitable for use as a primer under cellulose finishes. Universal colourants may be incompatible. A test sample is advised. Protect from frost.

Environmental Info.

Water based

**Tor Coatings Ltd,
Portobello Industrial Est,
Birtley,
Chester-le-Street,
Co Durham.
DH3 2RE**