

Stormshield Self-Cleaning Masonry

DESCRIPTION

Johnstone's Stormshield Self-Cleaning Masonry has been formulated using groundbreaking nano technology in order to give an extremely smooth and dirt resisting finish. Suitable for application to exterior cement rendering, rough cast, brick and concrete, the coating is also highly flexible.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Cement rendering, rough cast, brick and concrete.

COLOUR RANGE

Over 6,000 colours are available via the Johnstone's 32k Tinting System

FINISH

Matt

VOLUME SOLID

30%

COVERAGE



Johnstone's Stormshield Self-Cleaning Masonry will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 12 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **PROTECT FROM FROST.**

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99%
VOC'S (Volatile Organic Compounds) contribute to atmospheric pollution.
EU limit value for this product (Cat A/c): 75g/l(2007)/40g/l(2010).
This product contains max 15g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 30µm

KEY PROPERTIES

- Unique nano particle technology
- Flexible, dirt resisting smooth finish
- 15 years life expectancy

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Treat fungal or algal growth with Fungicidal Wash as directed. Seal absorbent surfaces with a coat of Stormshield Self-Cleaning Masonry, thinned up to 10% with clean water. Wear a suitable face mask when creating dust. For additional information and free Johnstone's Trade datasheets call 01924 354000 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or long pile roller. Do not apply in temperatures below 5°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

5 Litre, 10 Litre

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.